



Conical washers

Dimensions

| for screws of | d H14 | D h14 | s | h min.-max | Weight kg/1000 pcs. | Packaging |
|---------------|----------|----------|------|---------------|------------------------|-----------|
| M 2 | 2,20 | 5,00 | 0,40 | 0,50-0,60 | 0,050 | 10.000 |
| M 2,5 | 2,70 | 6,00 | 0,50 | 0,61-0,72 | 0,090 | 10.000 |
| M 3 | 3,20 | 7,00 | 0,60 | 0,72-0,85 | 0,140 | 10.000 |
| M 3,5 | 3,70 | 8,00 | 0,80 | 0,92-1,06 | 0,250 | 10.000 |
| M 4 | 4,30 | 9,00 | 1,00 | 1,12-1,30 | 0,380 | 5.000 |
| M 5 | 5,30 | 11,00 | 1,20 | 1,35-1,55 | 0,690 | 2.500 |
| M 6 | 6,40 | 14,00 | 1,50 | 1,70-2,00 | 1,430 | 2.500 |
| M 8 | 8,40 | 18,00 | 2,00 | 2,24-2,60 | 3,130 | 1.000 |
| M 10 | 10,50 | 23,00 | 2,50 | 2,80-3,20 | 6,450 | 500 |
| M 12 | 13,00 | 29,00 | 3,00 | 3,43-3,95 | 12,400 | 250 |
| M 14 | 15,00 | 35,00 | 3,50 | 4,04-4,65 | 21,600 | 100 |
| M 16 | 17,00 | 39,00 | 4,00 | 4,58-5,25 | 30,400 | 100 |
| M 18 | 19,00 | 42,00 | 4,50 | 5,08-5,80 | 38,900 | 100 |
| M 20 | 21,00 | 45,00 | 5,00 | 5,60-6,40 | 48,800 | 100 |
| M 22 | 23,00 | 49,00 | 5,50 | 6,15-7,05 | 63,500 | 100 |
| M 24 | 25,00 | 56,00 | 6,00 | 6,77-7,75 | 92,900 | 50 |
| M 27 | 28,00 | 60,00 | 6,50 | 7,30-8,35 | 113,00 | 50 |
| M 30 | 31,00 | 70,00 | 7,00 | 8,00-9,20 | 170,00 | 50 |

Hardness: 430-490 HV

plain oiled

mech. zinc plated

ZincFlake

other finishes on request

rechnical specifications according to DIN 267