



ASME B 18 21 1 2009 HEAVY
CARBON STEEL
STAINLESS STEEL AISI 304 / 316

Split Lock Washers

DIMENSIONS in inch

nominal size	d max.	d min.	D max.	Thickness min.	Width min.	kg/1.000 pcs	Packing Unit BULK 9"x9"x5 1/2"
#10 = 3/16"	0,200	0,193	0,350	0,056	0,070	0,40	30.000
#12 (0.216)	0,227	0,220	0,391	0,063	0,077	0,55	20.000
1/4"	0,260	0,252	0,489	0,077	0,110	1,17	12.000
5/16"	0,322	0,314	0,593	0,097	0,130	2,11	6.000
3/8"	0,385	0,377	0,688	0,115	0,145	3,34	4.000
7/16"	0,450	0,440	0,784	0,133	0,160	4,84	3.000
1/2"	0,512	0,502	0,879	0,151	0,176	6,83	2.000
9/16"	0,574	0,564	0,975	0,170	0,193	9,37	1.500
5/8"	0,641	0,628	1,087	0,189	0,210	13,00	1.000
3/4"	0,766	0,753	1,285	0,226	0,244	21,00	600
7/8"	0,894	0,878	1,489	0,266	0,281	32,70	400
1"	1,024	1,003	1,700	0,306	0,319	48,80	300
1 1/8"	1,153	1,129	1,903	0,345	0,356	69,00	200
1 1/4"	1,280	1,254	2,104	0,384	0,393	93,00	150
1 3/8"	1,408	1,379	2,301	0,422	0,427	122,00	100
1 1/2"	1,534	1,504	2,491	0,458	0,458	154,00	75

Pallet size 36"x36".

Parts are bagged and then boxed.

16 cartons per layer, max 4 layers per pallet. Secured by a master cardboard box.

*packing for HDG may vary

Material

STAINLESS STEEL AISI 304 / AISI 316 Hardness: 345 - 420 Hv

CARBON STEEL Hardness: 372 - 458 Hv

other raw material on enquiry

Coatings:	plain oiled	black oxide	electro zinc plated white / yellow, baked
	hot dip galvanised*	zinc-flake	mechanical zinc plated white / yellow