

**ASME B 18 21 1 2009 HIGH COLLAR**

CARBON STEEL

STAINLESS STEEL AISI 304 / 316

Split Lock Washers**DIMENSIONS in inch**

nominal size	d max.	d min.	D max.	Thickness min.	Width min.	kg/1.000 pcs	Packing Unit BULK 9"x9"x5 1/2"
#8 = 5/32"	0,174	0,167	0,267	0,047	0,042	0,16	70.000
#10 = 3/16"	0,200	0,193	0,294	0,047	0,042	0,16	50.000
1/4"	0,260	0,252	0,363	0,078	0,047	0,35	30.000
5/16"	0,322	0,314	0,457	0,093	0,062	0,83	15.000
3/8"	0,385	0,377	0,550	0,125	0,076	1,68	7.000
7/16"	0,450	0,440	0,644	0,140	0,090	2,50	5.500
1/2"	0,512	0,502	0,733	0,172	0,103	4,10	3.500
5/8"	0,641	0,628	0,917	0,203	0,125	7,20	1.750
3/4"	0,766	0,753	1,105	0,218	0,154	11,70	1.000
7/8"	0,894	0,878	1,291	0,234	0,182	19,00	700
1"	1,024	1,003	1,478	0,250	0,208	23,80	500

Pallet size 36"x36".

Parts are bagged and then boxed.

16 cartons per layer, max 4 layers per pallet. Secured by a master cardboard box.

*packing for HDG may vary

Material

STAINLESS STEEL AISI 304 / AISI 316 Hardness: 345 - 420 Hv

CARBON STEEL Hardness: 372 - 458 Hv

other raw material on enquiry

Coatings:	plain oiled	black oxide	electro zinc plated white / yellow, baked
	hot dip galvanised*	zinc-flake	mechanical zinc plated white / yellow