ASME B 18 21 1 2009 HEAVY

CARBON STEEL

STAINLESS STEEL AISI 304 / 316

Split Lock Washers



DIMENSIONS in mm

nominal size	d max.	d min.	D max.	Thickness min.	Width min.	kg/1.000 pcs	Packing Unit BULK 9"x9"x51/2"
#10 = 3/16"	5,08	4,90	8,89	1,42	1,78	0,40	30.000
#12 (0.216)	5,77	5,59	9,93	1,60	1,96	0,55	20.000
1/4"	6,60	6,40	12,42	1,96	2,79	1,17	12.000
5/16"	8,18	7,98	15,06	2,46	3,30	2,11	6.000
3/8"	9,78	9,58	17,48	2,92	3,68	3,34	4.000
7/16"	11,43	11,18	19,91	3,38	4,06	4,84	3.000
1/2"	13,00	12,75	22,33	3,84	4,47	6,83	2.000
9/16"	14,58	14,33	24,77	4,32	4,90	9,37	1.500
5/8"	16,28	15,95	27,61	4,80	5,33	13,00	1.000
3/4"	19,46	19,13	32,64	5,74	6,20	21,00	600
7/8"	22,71	22,30	37,82	6,76	7,14	32,70	400
1"	26,01	25,48	43,18	7,77	8,10	48,80	300
1 1/8"	29,29	28,68	48,34	8,76	9,04	69,00	200
1 1/4"	32,51	31,85	53,44	9,75	9,98	93,00	150
1 3/8"	35,76	35,03	58,45	10,72	10,85	122,00	100
1 1/2"	38,96	38,20	63,27	11,63	11,63	154,00	75

Pallet size 36"x36".

Parts are bagged and then boxed.

16 cartons per layer, max 4 layers per pallet. Secured by a master cardboard box.

*packing for HDG may vary

Material

STAINLESS STEEL AISI 304 / AISI 316 Hardness: 345 - 420 Hv

CARBON STEEL Hardness: 372 - 458 Hv

other raw material on enquiry

Coatings:	plain oiled	black oxide	electro zinc plated white / yellow, baked
	hot dip galvanised*	zinc-flake	mechanical zinc plated white / yellow