


Spring washers
Dimensions

for screws of	d min.-max.	D max.	b min.-max.	s min.-max.	h min.-max.	Weight kg/1000 pcs.	Packaging
M 2	2,10-2,40	4,40	0,80-1,00	0,40-0,60	0,70-0,90	0,035	1.000
M 2,5	2,60-2,90	5,10	0,90-1,10	0,50-0,70	0,90-1,10	0,055	1.000
M 3	3,10-3,40	6,20	1,20-1,40	0,60-0,80	1,10-1,30	0,09	1.000
M 3,5	3,60-3,90	6,70	1,20-1,40	0,60-0,80	1,10-1,30	0,10	1.000
M 4	4,10-4,40	7,60	1,40-1,60	0,70-0,90	1,20-1,40	0,18	1.000
M 5	5,10-5,40	9,20	1,70-1,90	0,90-1,00	1,50-1,70	0,30	1.000
M 6	6,10-6,50	11,80	2,40-2,60	1,20-1,40	2,00-2,20	0,70	1.000
M 7	7,10-7,50	12,80	2,40-2,60	1,20-1,40	2,00-2,20	0,93	1.000
M 8	8,10-8,50	14,80	2,85-3,15	1,50-1,70	2,45-2,75	1,30	1.000
M 10	10,20-10,70	18,10	3,30-3,70	1,70-1,90	2,85-3,15	2,10	1.000
M 12	12,20-12,70	21,10	3,80-4,20	1,95-2,25	3,35-3,65	3,20	500
M 14	14,20-14,70	24,10	4,30-4,70	2,25-2,55	3,90-4,30	4,80	500
M 16	16,20-17,00	27,40	4,80-5,20	2,65-2,95	4,50-5,10	7,00	250
M 18	18,20-19,00	29,40	4,80-5,20	2,65-2,95	4,50-5,10	7,80	250
M 20	20,20-21,20	33,60	5,80-6,20	3,00-3,40	5,10-5,90	12,20	100
M 22	22,50-23,50	35,90	5,80-6,20	3,00-3,40	5,10-5,90	13,30	100
M 24	24,50-25,50	40,00	6,75-7,25	3,80-4,20	6,50-7,50	21,50	100
M 27	27,50-28,50	43,00	6,75-7,25	3,80-4,20	6,50-7,50	23,70	100
M 30	30,50-31,70	48,20	7,75-8,25	5,80-6,20	9,50-10,50	42,50	50
M 36	36,50-37,70	58,20	9,75-10,25	5,80-6,20	10,30-11,30	68,00	25
M 39	39,50-40,70	61,20	9,75-10,25	5,80-6,20	10,30-11,30	90,00	25
M 42	42,50-43,70	68,20	11,75-12,25	6,75-7,25	12,00-13,00	111,00	25
M 45	45,50-46,70	71,20	11,75-12,25	6,75-7,25	12,00-13,00	117,00	10
M 48	49,00-50,50	75,00	11,75-12,25	6,75-7,25	12,00-13,00	123,00	10
M 52	53,00-54,50	83,00	13,75-14,25	7,75-8,25	14,00-15,50	182,00	10
M 56	57,00-58,50	87,00	13,75-14,25	7,75-8,25	14,00-15,50	193,00	10

Hardness: 430-530 HV

plain oiled

mech. zinc plated

ZincFlake

other finishes on request