



**Conical washers**

**Dimensions**

for screws of	d H14	D h14	s	h min.-max	Weight kg/1000 pcs.	Packaging
M 2	2,20	5,00	0,40	0,50-0,60	0,050	10.000
M 2,5	2,70	6,00	0,50	0,61-0,72	0,090	10.000
M 3	3,20	7,00	0,60	0,72-0,85	0,140	10.000
M 3,5	3,70	8,00	0,80	0,92-1,06	0,250	10.000
M 4	4,30	9,00	1,00	1,12-1,30	0,380	5.000
M 5	5,30	11,00	1,20	1,35-1,55	0,690	2.500
M 6	6,40	14,00	1,50	1,70-2,00	1,430	2.500
M 8	8,40	18,00	2,00	2,24-2,60	3,130	1.000
M 10	10,50	23,00	2,50	2,80-3,20	6,450	500
M 12	13,00	29,00	3,00	3,43-3,95	12,400	250
M 14	15,00	35,00	3,50	4,04-4,65	21,600	100
M 16	17,00	39,00	4,00	4,58-5,25	30,400	100
M 18	19,00	42,00	4,50	5,08-5,80	38,900	100
M 20	21,00	45,00	5,00	5,60-6,40	48,800	100
M 22	23,00	49,00	5,50	6,15-7,05	63,500	100
M 24	25,00	56,00	6,00	6,77-7,75	92,900	50
M 27	28,00	60,00	6,50	7,30-8,35	113,00	50
M 30	31,00	70,00	7,00	8,00-9,20	170,00	50
M 36*	37,00	84,00	8,00	9,00-10,20	280,00	25

Hardness: 430-490 HV  
 plain oiled  
 mech. zinc plated  
 ZincFlake  
 other finishes on inquiry  
 technical specifications according to DIN 267  
 \*special part. Raw material 42CrMo4