



Abmessung	Maße					Gewicht	Verpackung			
für Schrauben von	d min.-max.	D max.	b min.-max.	s min.-max.	h min.-max.	kg/1.000 Stück	Verpackungs- einheit	Masterkarton	Menge 2 Holzrahmen	Menge Europalette
M 2	2,10-2,30	4,30	0,80-1,00	0,40-0,60	1,00-1,20	0,035	1.000	100.000	3.000.000	4.500.000
M 2,2	2,30-2,50	4,70	0,90-1,10	0,50-0,70	1,00-1,20	0,052	1.000	100.000	3.000.000	4.500.000
M 2,5	2,60-2,80	5,00	0,90-1,10	0,50-0,70	1,20-1,40	0,056	1.000	100.000	3.000.000	4.500.000
M 3	3,10-3,30	6,10	1,20-1,40	0,70-0,90	1,60-1,90	0,115	1.000	80.000	2.400.000	3.600.000
M 3,5	3,60-3,80	6,60	1,20-1,40	0,70-0,90	1,60-1,90	0,130	1.000	80.000	2.400.000	3.600.000
M 4	4,10-4,35	7,55	1,40-1,60	0,80-1,00	1,80-2,10	0,180	1.000	50.000	1.500.000	2.250.000
M 5	5,10-5,35	9,15	1,70-1,90	1,10-1,30	2,40-2,80	0,360	1.000	25.000	750.000	1.125.000
M 6	6,10-6,40	11,70	2,35-2,65	1,50-1,70	3,20-3,80	0,830	1.000	15.000	450.000	675.000
M 8	8,20-8,55	14,85	2,85-3,15	1,90-2,10	4,00-4,70	1,620	1.000		396.000	396.000
M 10	10,20-10,60	18,00	3,30-3,70	2,05-2,35	4,40-5,20	2,540	1.000		198.000	264.000
M 12	12,20-12,60	21,00	3,80-4,20	2,35-2,65	5,00-5,90	3,880	500		132.000	165.000
M 14	14,20-14,70	24,10	4,30-4,70	2,85-3,15	6,00-7,10	6,040	500		66.000	99.000
M 16	16,30-16,90	27,30	4,80-5,20	3,30-3,70	7,00-8,30	8,920	250		49.500	66.000
M 18	18,30-19,00	29,40	4,80-5,20	3,30-3,70	7,00-8,30	9,750	250		49.500	66.000
M 20	20,30-21,10	33,50	5,80-6,20	3,80-4,20	8,00-9,40	15,10	100		26.400	33.000
M 22	22,40-23,30	35,70	5,80-6,20	3,80-4,20	8,00-9,40	16,30	100		26.400	33.000
M 24	24,40-25,30	39,80	6,75-7,25	4,80-5,20	10,00-11,80	26,30	100		13.200	19.800
M 27	27,50-28,50	43,00	6,75-7,25	4,80-5,20	10,00-11,80	28,90	100		13.200	19.800
M 30	30,50-31,70	48,20	7,75-8,25	5,80-6,20	12,00-14,20	44,30	50		6.600	9.900
M 36	36,50-37,70	58,20	9,75-10,25	5,80-6,20	12,00-14,20	67,30	25			
M 39	39,50-40,70	61,20	9,75-10,25	5,80-6,20	12,00-14,20	71,70	25			
M 42	42,50-43,70	68,20	11,75-12,25	6,75-7,25	14,00-16,50	111,00	25			
M 45	45,50-46,70	71,20	11,75-12,25	6,75-7,25	14,00-16,50	117,00	25			
M 48	49,00-50,50	75,00	11,75-12,25	6,75-7,25	14,00-16,50	123,00	25			
M 52	53,00-54,50	83,00	13,75-14,25	7,75-8,25	16,00-18,90	182,00	10			

Härte: 430-530 HV

Oberflächen:

roh gefettet

galvanisch verzinkt

mechanisch verzinkt

Zinklamelle

feuerverzinkt

andere Oberflächenausführungen auf Anfrage