



DOUBLE TOOTHED LOCK WASHERS

DF NFE 27626

SPRING STEEL C60

Measurement	Dimension						Weight	Packaging			
for screws	d min.-max.	D min.-max.	s min.-max.	min.-max.	internal teeth	external teeth	kg / 1000 pcs	packaging	masterbox	quantity 2 wooden frames	quantity euro pallet
M 4.0	4.20-4.38	15.17-15.60	0.80	2.00-2.80	7	16	1.10	1.000	40.000	1.200.000	1.800.000
M 5.0	5.10-5.28	17.47-17.90	0.80	2.00-2.80	7	16	1.45	1.000		264.000	330.000
M 6.0	6.10-6.32	17.70-18.20	0.90	2.25-3.15	8	16	1.53	1.000		198.000	264.000
M 8.0	8.20-8.42	21.73-22.25	1.00	2.50-3.50	10	16	2.49	500		99.000	132.000
M 10.0	10.20-10.47	25.58-26.10	1.10	2.60-3.85	12	18	4.15	250		49.500	66.000
M 12.0	12.50-12.77	29.78-30.30	1.20	3.00-4.20	12	18	5.40	250		49.500	66.000
M 16.0	16.30-16.73	35.48-36.10	1.40	3.50-4.90	12	20	8.70	100		19.800	26.400

Hardness: 430-510 HV

surfaces:

plain oiled

zinc plated

other finishes on request