



Abmessung	Maße					Gewicht	Verpackung			
für Schrauben von	d min.-max.	D max.	b min.-max.	s min.-max.	h min.-max.	kg/1.000 Stück	Verpackungs- einheit	Masterkarton	Menge 2 Holzrahmen	Menge Europalette
M 56	57,00-58,20	87,00	13,75-14,25	7,75-8,25	16,00-18,90	193				
M 60	61,00-62,50	91,00	13,75-14,25	7,75-8,25	16,00-18,90	203				
M 64	65,00-66,50	95,00	13,75-14,25	7,75-8,25	16,00-18,90	218				
M 68	69,00-70,50	99,00	13,75-14,25	7,75-8,25	16,00-18,90	228				
M 72	73,00-74,50	103,00	13,75-14,25	7,75-8,25	16,00-18,90	240				
M 80	81,00-82,50	111,00	13,75-14,25	7,75-8,25	16,00-18,90	262				
M 90	91,00-92,50	121,00	13,75-14,25	7,75-8,25	16,00-18,90	290				
M 100	101,00-102,50	131,00	13,75-14,25	7,75-8,25	16,00-18,90	318				

Härte: 430-530 HV

Oberflächen:

roh gefettet

galvanisch verzinkt

mechanisch verzinkt

Zinklamelle

feuerverzinkt

andere Oberflächen Ausführungen auf Anfrage