



Measurement	Dimensions				static load	Weight	Packaging			
for screws of	d min.-max.	D min.-max.	s min.-max.	d ₅ min.-max.	max. KN	kg/1000 pcs.	packaging	masterbox	quantity 2 wooden frames	quantity euro pallet
M 6	7,10-7,32	11,80-12,20	2,70-2,90	10,80-11,20	9	1,40	1.000			
M 8	9,60-9,82	16,80-17,20	3,40-3,60	14,30-14,70	17	3,80	1.000			
M 10	12,00-12,27	20,80-21,20	4,10-4,30	18,30-18,70	26	6,50	500			
M 12	14,20-14,47	23,80-24,20	4,90-5,10	19,80-20,20	38	10,60	250			
M 14	16,50-16,77	27,80-28,20	5,50-5,70	24,60-25,00	53	15,50	200			
M 16	19,00-19,33	29,80-30,20	6,10-6,30	25,80-26,20	73	18,70	100			
M 20	23,20-23,53	35,70-36,30	7,30-7,70	30,70-31,30	117	32,00	50			
M 24	28,00-28,33	43,70-44,30	9,30-9,70	36,70-37,30	168	63,00	50			
M 30	35,00-35,39	55,70-56,30	11,80-12,20	48,70-49,30	269	130,00	50			
M 36	42,00-42,39	67,70-68,30	14,80-15,20	59,70-60,30	394	236,00	25			
M 42	49,00-49,39	77,70-78,30	17,80-18,20	69,70-70,30	542	365,00	10			
M 48	56,00-56,46	91,70-92,30	21,80-22,20	81,70-82,30	714	643,00	10			

carbon steel, case hardened at a depth of 0.2-0.4 mm with a surface hardness of 550-650 HV 10

surfaces:

burnished and slightly oiled

electro zinc plated

ZincFlake

other finishes on request