



Abmessung	Maße					Gewicht	Verpackung			
für Schrauben von	d min.-max.	D ≈	b min.-max.	s min.-max.	h = 2s	kg/1.000 Stück	Verpackungs- einheit	Masterkarton	Menge 2 Holzrahmen	Menge Europalette
M 3	3,50-3,98	5,20	0,80-1,20	0,40-0,80	1,20	0,07	1.000	50.000	1.500.000	2.250.000
M 4	4,50-4,98	7,30	0,80-1,20	0,80-1,20	2,00	0,22	1.000	50.000	1.500.000	2.250.000
M 5	5,50-5,98	8,30	1,30-1,70	0,80-1,20	2,00	0,26	1.000	25.000	750.000	1.125.000
M 6	6,50-7,08	10,40	1,80-2,20	1,00-1,40	2,40	0,50	1.000	15.000	450.000	675.000
M 7	7,50-8,08	11,40	1,80-2,20	1,00-1,40	2,40	0,56	1.000	15.000	450.000	675.000
M 8	8,50-9,08	13,40	2,30-2,70	1,30-1,70	3,00	1,00	1.000		396.000	396.000
M 10	10,50-11,20	16,50	2,80-3,20	1,60-2,00	3,60	1,79	1.000		264.000	330.000
M 12	13,00-13,70	20,00	3,26-3,74	1,80-2,20	4,00	2,85	500		132.000	165.000
M 14	15,00-15,70	23,00	3,76-4,24	2,30-2,70	5,00	4,80	500		66.000	99.000
M 16	17,00-17,70	25,00	3,76-4,24	2,30-2,70	5,00	5,30	250		49.500	66.000
M 18	19,00-19,84	29,00	4,76-5,24	2,80-3,20	6,00	9,00	250		49.500	66.000
M 20	21,00-21,84	31,00	4,76-5,24	2,80-3,20	6,00	9,80	100		26.400	33.000
M 22	23,00-23,84	33,00	4,76-5,24	2,80-3,20	6,00	10,50	100		13.200	19.800
M 24	25,00-25,84	37,00	5,76-6,24	3,26-3,74	7,00	16,20	100		13.200	19.800
M 27	28,00-28,84	40,00	5,76-6,24	3,26-3,74	7,00	17,80	100		13.200	19.800
M 30	31,00-32,00	45,00	6,71-7,29	4,26-4,74	9,00	29,80	50		6.600	9.900

Härte: 430-510 HV

Oberflächen:

roh gefettet

galvanisch verzinkt

andere Oberflächenausführungen und Werkstoffe auf Anfrage