



Dimensions and Specifications

For screws of	d min.-max.	D max.	s min.-max.	b min. max.	h min.-max.	Weight kg/1000 pcs.	Packaging	Masterkarton	Menge 2 Holzrahmen	Menge Europalette	
4	4,10-4,40	7,60	0,70-0,90	1,40-1,60	1,20-1,40	0,15	1.000	50.000	1.500.000	2.250.000	
5	5,10-5,40	9,20	0,90-1,10	1,70-1,90	1,50-1,70	0,30	1.000	25.000	750.000	1.125.000	
6	6,10-6,40	11,80	1,20-1,40	2,35-2,65	2,00-2,20	0,70	1.000	15.000	450.000	675.000	
8	8,10-8,40	14,80	1,50-1,70	2,85-3,15	2,45-2,75	1,30	1.000		396.000	396.000	
10	10,20-10,70	18,10	1,70-1,90	3,30-3,70	2,85-3,15	2,10	1.000		198.000	264.000	
12	12,20-12,70	21,10	1,95-2,25	3,80-4,20	3,35-3,65	3,20	500		132.000	165.000	
14	14,20-14,70	24,10	2,25-2,55	4,30-4,70	3,90-4,30	4,80	250		99.000	132.000	
16	16,20-17,00	27,40	2,65-2,95	4,80-5,20	4,50-5,10	7,00	250		66.000	82.500	
18	18,20-19,00	29,40	2,65-2,95	4,80-5,20	4,50-5,10	7,80	250		49.500	66.000	
20	20,20-21,20	33,60	3,00-3,40	5,80-6,20	5,10-5,90	12,20	100		39.600	39.600	
22	22,50-23,50	35,90	3,00-3,40	5,80-6,20	5,10-5,90	13,30	100		26.400	33.000	
24	24,50-25,50	40,00	3,80-4,20	6,80-7,20	6,50-7,50	21,50	100		19.800	26.400	
27	27,50-28,50	43,00	3,80-4,20	6,80-7,20	6,50-7,50	23,70	100		19.800	26.400	
30	30,50-31,70	84,20	5,80-6,20	7,80-8,20	9,50-10,50	42,50	50		9.900	13.200	
Special features:		grid shaped surface ("Sperrkanten") wire profile alternately bend apex of the dome between 135°-150° 5-times deflected								technical specifications according to DIN 128 and BN 208012-6 equals VSK	
Finishings:		oiled mechanical plated zinc-flake coating other coatings on inquiry									