



toothed form "K"

For screws of	d min.-max.	D max.	s min.-max.	h min. - max	Weight kg/1000 pcs.	Number of Sperrkanten	Tightening Torque (Nm) 0.18 µ	Packaging	masterbox	quantity 2 wooden frames	quantity euro pallet
4	4.10-4.40	7.80-8.20	0.97-1.03	1.20-1.35	0.250	16	2,8	1.000	25.000	750.000	1.125.000
5	5.10-5.40	9.80-10.20	0.97-1.03	1.25-1.50	0.410	20	5,3	1.000	25.000	750.000	1.125.000
6	6.10-6.40	11.80-12.20	1.16-1.24	1.50-1.80	0.710	20	9,1	1.000	15.000	450.000	675.000
8	8.20-8.50	15.80-16.20	1.36-1.44	1.90-2.40	1.500	24	21,8	1.000		264.000	330.000
10	10.20-10.56	19.75-20.25	1.56-1.64	2.15-2.60	2.680	24	44,0	1.000		132.000	198.000
12	12.40-12.80	23.75-24.25	1.56-1.64	2.15-2.60	3.850	24	75,0	500		132.000	165.000

The tightening torques listed below are only valid as an indication - referring to VDI 2230.

Raw material: stainless and acid-proofed steel, material A4