



Für Schrauben von	d min.-max.	D min.-max.	s min.-max.	h min.-max.	Gewicht kg/1000 St.	Anzahl Sperrkanten	Anziehdrehmoment (Nm) 8.8	Anziehdrehmoment (Nm) 10.9	Verpackungseinheit	Masterkarton	Menge 2 Holzrahmen	Menge Europalette
----------------------	----------------	----------------	----------------	----------------	------------------------	--------------------	------------------------------	-------------------------------	--------------------	--------------	-----------------------	----------------------

mittlere Form "M" SKSM

4	4.10-4.40	9.80-10.20	0.95-1.05	1.25-1.50	0.470	16	3,3	4,9	1.000	25.000	750.000	1.125.000
5	5.10-5.40	11.80-12.20	1.16-1.24	1.55-1.90	0.790	20	6,7	9,8	1.000	15.000	450.000	675.000
6	6.10-6.40	13.77-14.20	1.36-1.44	1.85-2.20	1.240	20	11,5	16,5	1.000		396.000	396.000
8	8.20-8.56	17.68-18.20	1.36-1.44	1.95-2.40	2.030	24	27,0	40,0	1.000		264.000	330.000
10	10.20-10.56	21.73-22.25	1.55-1.65	2.25-2.75	3.490	24	54,0	79,0	1.000		132.000	198.000
12	12.40-12.83	26.73-27.25	1.75-1.85	2.60-3.10	6.010	24	92,0	135,0	500		66.000	99.000
14	14.40-14.83	29.63-30.25	2.34-2.46	3.20-3.70	9.370	24	145,0	215,0	250		49.500	66.000
16	16.40-16.83	31.88-32.50	2.44-2.56	3.45-3.95	10.650	28	225,0	330,0	250		33.000	49.500
18	18.50-19.25	34.38-35.00	2.94-3.06	4.00-4.50	15.200	28	320,0	460,0	250		31.500	31.500
20	21.00-21.75	39.38-40.00	2.94-3.06	4.20-4.70	20.400	30	460,0	650,0	100		19.800	26.400
22	23.00-23.75	44.38-45.00	3.44-3.56	4.80-5.30	30.400	30	620,0	890,0	100		13.200	19.800
24	25.00-25.75	49.38-50.00	3.44-3.56	5.10-5.60	38.200	32	790,0	1.120,0	50		9.900	13.200
27	28.00-28.85	59.26-60.00	3.91-4.09	6.10-6.60	69.000	36	1.160,0	1.650,0	25		6.600	8.250
30	31.00-31.85	69.26-70.00	4.41-4.59	7.30-7.80	109.000	36	1.550,0	2.250,0	25		3.300	4.950

schmale Form "S" SKSS

4	4.10-4.40	7.80-8.20	0.95-1.05	1.15-1.40	0.270	16	2,0	-	1.000	50.000	1.500.000	2.250.000
5	5.10-5.40	9.80-10.20	0.95-1.05	1.25-1.50	0.400	20	4,0	-	1.000	25.000	750.000	1.125.000
6	6.10-6.40	11.77-12.20	1.16-1.24	1.55-1.85	0.707	20	7,0	-	1.000	15.000	450.000	675.000
8	8.20-8.56	15.77-16.20	1.36-1.44	1.90-2.40	1.500	24	16,5	-	1.000		396.000	396.000
10	10.20-10.56	19.73-20.25	1.55-1.65	2.10-2.60	2.640	24	32,0	-	1.000		198.000	264.000
12	12.40-12.83	23.73-24.25	1.55-1.65	2.20-2.70	3.870	24	57,0	-	500		132.000	165.000

breite Form "B" SKSB

6	6.10-6.40	17.68-18.20	1.36-1.44	2.15-2.55	2.470	20	16,5	19,5	1.000		264.000	330.000
8	8.20-8.56	21.73-22.25	1.84-1.96	2.60-3.00	4.880	24	40,0	47,0	500		99.000	132.000
10	10.20-10.56	26.73-27.25	2.34-2.46	3.20-3.70	9.200	24	79,0	92,0	1.000		84.000	84.000
12	12.40-12.83	31.68-32.30	2.74-2.86	4.10-4.60	14.620	24	135,0	158,0	500		35.000	35.000

für Zylinderschrauben Form "Z" SKSZ

6	6.10-6.40	9.54-9.90	1.36-1.44	1.50-1.80	0.409	20	11,5	16,5	1.000	20.000	600.000	900.000
8	8.20-8.56	12.34-12.70	1.36-1.44	1.55-1.85	0.670	24	27,0	40,0	1.000	10.000	300.000	450.000
10	10.20-10.56	15.74-16.10	1.55-1.65	1.85-2.20	1.299	24	54,0	79,0	1.000		264.000	330.000
12	12.40-12.83	17.78-18.30	1.75-1.85	2.05-2.45	1.650	24	92,0	135,0	500		198.000	198.000
14	14.40-14.83	20.88-21.40	2.34-2.46	2.70-3.10	3.000	24	145,0	215,0	250		132.000	165.000
16	16.40-16.83	24.08-24.60	2.44-2.56	2.90-3.30	4.400	28	225,0	330,0	250		99.000	99.000

Die aufgeführten Anziehdrehmomente gelten nur als unverbindliche Richtwerte - siehe VDI 2230.

Ausführungen: roh gefettet
Zinklamelle
andere Oberflächenausführungen auf Anfrage