


DIMENSIONS AND SPECIFICATIONS

For screws of	d min.-max.	D max.	s min.-max.	b min.-max.	h min.	Weight kg/1000 pcs.	Packaging	Masterkarton	Menge 2 Holzrahmen	Menge Europalette
2,5	2,60-2,90	5,10	0,50-0,70	0,90-1,10	1,00	0,05	1.000	80.000	2.400.000	3.600.000
3	3,10-3,40	6,20	0,70-0,90	1,20-1,40	1,30	0,11	1.000	80.000	2.400.000	3.600.000
4	4,10-4,40	7,60	0,80-1,00	1,40-1,60	1,40	0,15	1.000	50.000	1.500.000	2.250.000
5	5,10-5,40	9,20	1,10-1,30	1,70-1,90	1,80	0,36	1.000	25.000	750.000	1.125.000
6	6,10-6,50	11,80	1,50-1,70	2,35-2,65	2,40	0,83	1.000	15.000	450.000	675.000
8	8,10-8,50	14,80	1,90-2,10	2,85-3,15	3,00	1,60	1.000		396.000	396.000
10	10,10-10,60	18,00	2,05-2,35	3,30-3,70	3,40	2,50	1.000		198.000	264.000
12	12,10-12,60	21,00	2,35-2,65	3,80-4,20	3,90	3,80	500		132.000	165.000
14	14,10-14,60	24,00	2,85-3,15	4,30-4,70	4,70	6,00	500		99.000	132.000
16	16,10-16,90	27,30	3,30-3,70	4,80-5,20	5,50	8,90	250		66.000	82.500
18	18,20-19,00	29,40	3,30-3,70	4,80-5,20	5,50	9,70	250		49.500	66.000
20	20,20-21,20	33,60	3,80-4,20	5,80-6,20	6,30	15,20	100		26.400	33.000
24	24,50-25,50	40,00	4,80-5,20	6,75-7,25	6,30	26,20	100		19.800	26.400

Special Features:

wire profile alternately bend
apex dome between 135°-150°
5-times deflected

technical specifications
according to DIN 128

SN 60727

equals to VHD

Raw material:

stainless and acid-proofed steel, raw-material 1.4310
high stainless and high acid-proofed steel, raw-material 1.4401